

OUTRIGGER PADS

Drillers - Backhoes - Utilities

Super Strong, Pads Are Engineered Light Weight, Composite Fiberglass.

Takes Up Less Space.

They Are Not As Thick, Or Heavy When Compared to Other Materials.

Design Features A Non-skid Surface, Superior Traction, And Enhanced Finish For Improved Durability.

Rope Handles For Easy Set-up.

No Water Absorption. Won't Rot.

Lighter weight.

1 year Limited Warranty.



Popular Models:

2424HDS (24" Square) Every Day Use.
Weight 12 Lbs. Equipment Under 25,000 Lbs.

3232HDS (32" Square) Every Day Use.
Weight 30 Lbs. Backhoes under 25,000 Lbs.

1818 (18" Square) Normal Field Use.
Weight 12 Lbs. Equipment up to 35,000 Lbs.

2424 (24" Square) Rough Field Use.
Weight 20 Lbs. Most Popular Line of Truck Pads.

3232 (32" Square) Demanding Field Use.
Weight 38 Lbs. Tandem Equipment up to 70,000 Lbs.



SVE Portable Roadway Systems, Inc
6128 -F Brookshire Blvd.
Charlotte, NC 28216

Ph: 704.398.0007
Fax: 704.398.0540

800.762.8267

sales@mudtraks.com
www.mudtraks.com

CRANE PADS

Standard Sizes: 24, 32, 36, 45 Inches Square.

Custom Sizes Available

Recommended Outrigger Pad Size for Equipment:

Our Outrigger Pad Size (sq.)	Weight (lbs) per pad	Model #	Equipment Weight	Outrigger Size
24"	20	24CR-7	22 ton	16"
	25	24CR-8	30 ton	16"
	30	24CR-10	40 ton	16"
32"	38	32CR-7	40 ton	22"
	42	32CR-8	50 ton	22"
	45	32CR-10	60 ton	22"
36"	42	36CR-7	60 ton	24"
	48	36CR-8	70 ton	24"
	55	36CR-10	90 ton	24"
45"	73	45CR-7	60 ton	32"
	80	45CR-8	80 ton	32"
	100	45CR-10	100 ton	32"

Thickness: Determined By Equipment Weight and Lift Capacity.

Pad Thickness: -7's are 0.60" -8's are 0.65" -10's are 0.70"

Cribbing Blocks May Be Required. Contact Us For Further Details And Sizing.



SVE Portable Roadway Systems, Inc

6128 -F Brookshire Blvd
Charlotte, NC 28216

Ph: 704.398.0007
Fax: 704.398.0540

800.762.8267

sales@mudtraks.com
www.mudtraks.com